

## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification<sup>5</sup> :

A61B 5/14

A1

(11) International Publication Number:

WO 93/19671

(43) International Publication Date:

14 October 1993 (14.10.93)

(21) International Application Number: PCT/GB93/00650

(22) International Filing Date: 30 March 1993 (30.03.93)

(30) Priority data:

9207120.8

1 April 1992 (01.04.92)

GB

(71) Applicant (for all designated States except US): OWEN MUMFORD LIMITED [GB/GB]; Brook Hill, Woodstock, Oxford OX20 1TU (GB).

(72) Inventors; and

(75) Inventors/Applicants (for US only): MARSHALL, Jeremy [GB/GB]; 16 Cranham Street, Jericho, Oxford OX2 6DD (GB). CROSSMAN, David, Danvers [GB/GB]; The Tower, Christmas Common, Oxford OX9 5HL (GB).


(74) Agents: LAINE, Simon, James et al.; Wynne-Jones, Laine &amp; James, 22 Rodney Road, Cheltenham, Gloucestershire GL50 1JJ (GB).

(81) Designated States: AU, BR, CA, JP, KR, RU, US, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).

Published

With international search report.

(54) Title: BLOOD SAMPLING DEVICE



(57) Abstract

A blood sampling device has a tubular body (1, 2) housing a spring loaded (7) lancet (8) whose needle (17) is initially protected by a cap (20) which projects out from the forward end of the body. A rocker-like trigger (9) is formed as part of the moulded body (1, 2) and holds the lancet (8) in a retracted position when the lancet is pushed back by the projecting cap (20). The cap can then be removed by a twist and pull action, breaking it free from the lancet body, which is prevented from rotating. Pressure on the trigger (9) releases the lancet (8), which is shot forward by the spring (7) for momentary projection of the needle tip (19), and then retracts to bring the needle tip within the body.

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	FR	France	MR	Mauritania
AU	Australia	GA	Gabon	MW	Malawi
BB	Barbados	GB	United Kingdom	NL	Netherlands
BE	Belgium	GN	Guinea	NO	Norway
BF	Burkina Faso	GR	Greece	NZ	New Zealand
BG	Bulgaria	HU	Hungary	PL	Poland
BJ	Benin	IE	Ireland	PT	Portugal
BR	Brazil	IT	Italy	RO	Romania
CA	Canada	JP	Japan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SK	Slovak Republic
CI	Côte d'Ivoire	LI	Liechtenstein	SN	Senegal
CM	Cameroon	LK	Sri Lanka	SU	Soviet Union
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	MC	Monaco	TG	Togo
DE	Germany	MG	Madagascar	UA	Ukraine
DK	Denmark	ML	Mali	US	United States of America
ES	Spain	MN	Mongolia	VN	Viet Nam
FI	Finland				

## Blood sampling device

This invention relates to blood sampling devices, and in particular to a pricker to draw a small drop of blood for analysis. Such prickers are widely used by diabetics, for example, who need to know their sugar level. However, there are many other applications.

These days, with AIDS, there is widespread concern surrounding the use of needles and their part in transmitting disease. Once a needle has been used on an infected person, subsequent use or an accidental prick on another could be fatal.

There is therefore a growing demand for a pricker which can be used just once and, having been used, is automatic-ally rendered safe for carriage and disposal.

Several such prickers have been proposed, for example in EP-A-0427406 and EP-A-0433050. These work well, and use a lancet which has been in production for many years. However, it is important for disposable objects with a very transient life to be made as simply and cheaply as possible, without compromising on effectiveness. This the present invention aims to do.

According to the present invention there is provided a disposable pricker comprising an elongate body with a spring-loaded lancet carried therein, the lancet tip normally being within the body, a trigger mechanism to retain the lancet in a fully retracted position energising the spring means and actuatable to release the lancet to cause

the tip to have a momentary position projecting from the forward end of the body, and an elongate cap encasing the lancet tip and having a head external of the body, the cap providing means to retract the lancet and being breakable  
5 free of the lancet to leave the tip exposed.

Conveniently, the trigger mechanism comprises a rocker with an outwardly projecting portion for manual operation and an inwardly projecting portion for co-operation with the lancet. The rocker may be centrally connected to the main part of the body by small webs which are  
10 distortable to allow the rocker action.

It has been found beneficial for the rocker to have further means connecting it to the body to resist pivoting below a predetermined actuating force. This  
15 prevents accidental operation.

Preferably the trigger mechanism is formed integrally with the body, which will generally be moulded in plastics material with a certain resilience. As the lancet is pushed back to prime the device, a projection on it can  
20 snap past an inwardly projecting lug on one end of the trigger and this will temporarily hold the lancet retracted. Pressure on the other end of the trigger will raise the lug clear and release the lancet.

Although the body and trigger will preferably be  
25 integral, they may initially be moulded as two main parts, one of which contains the trigger, connected by a thin flexible web, presenting the body in an opened out condition. When the lancet and spring means are in place, these

two parts will be folded together and secured, as by adhesive or ultrasonic welding.

In order to assist in breaking the cap away from the lancet, the latter may have an engagement with the interior of the body that prevents it rotating about its longitudinal axis, at least when the lancet is retracted. The cap may therefore be twisted off by one hand with the other holding the body.

Another characteristic of the fit of the lancet within the body is preferably that, once the lancet has been fired, it should tend to lie skew to the axis of the body. This would make it difficult, using the twisted off cap for example, to insert it again and press the lancet back for possible re-use.

For a better understanding of the invention, one embodiment will now be described, by way of example, with reference to the accompanying drawing, in which:

Figure 1 is a longitudinal section of a blood sampling pricker,

Figure 2 is a plan view of the pricker of Figure 1, and

Figure 3 is a cross-section on the line III-III of Figure 1.

The body of the pricker is of generally square tubular form and is of moulded plastics construction. Two channel-like parts 1 and 2 are closed together and secured in a plane A to form the tube, which is closed at the rear end 3 and which has an opening 4 at the forward end. An external

bevel 5 around this opening forms a shallow recess into which a thumb or finger, for example, can be pressed for pricking.

The parts 1 and 2 have interior lugs 6 opposing each other close to the rear end 3 to provide a trap for one end of a coil spring 7 by which a lancet 8, to be described in more detail below, is made captive. Otherwise, the lower part 2 is plain. However, the upper part 1 has a trigger 9 integrally moulded with it. The trigger lies largely within a bottle shaped aperture 10, the head of the bottle pointing forwards, and in plan view the trigger 9 is similarly shaped but smaller. Its main connection to the part 1 is by short bridges or webs 11 at the shoulders of the "bottle" and in the normal, relaxed state, the pricker adopts the position shown in Figure 1. In that case, the forward end of the trigger, in front of the webs 11, is generally flush with the interior of the upper part of the body 1, but at its leading end a hook 12 projects down into the body cavity. The hook 12 has a shallow slope facing forwards and a steep rear face. To the rear of the webs 11, the pricker 9 steps upwardly to a thumb pad 13 by which it can be pivoted, and there are two optional thin L-shaped strips 14 connecting the rear corners of this pad 13 to the main part 1 of the body. When the pad 13 is pressed, these strips 14 (if provided) buckle or shear off at their connection to the rear end 3 and the trigger pivots to move the hook 12 out clear of the interior of the body 1. Longitudinal reinforcing ribs 15 and 16 make the trigger 9 an effectively rigid

rocker.

The strips 14 are not necessary if the device is to be provided with the lancet 8 as shown in Figures 1 and 2 and as described below, when it has to be cocked by the user before release. But there is also a call for pre-cocked devices and then there is a need to prevent premature actuation of the trigger, as by careless handling for example. The strips 14 perform this safety function, since they demand a very positive pressure on the pad 13. They will generally buckle or shear suddenly, giving a quick action of the trigger and clean release of the lancet. A pre-cocked lancet will still usually have a cap, as described below, to maintain sterility of the needle.

The lancet 8 comprises a steel needle 17 almost entirely encased in a cruciform-section jacket 18, except for its tip 19. Initially, this tip is concealed within the rear end of an elongated cap 20 joined to the jacket 18 by a weak collar 21. The cap 20 passes freely through the aperture 4 and terminates outside the body 1 in a tab 22.

Just to the rear of the collar 21, the jacket 18 terminates at its forward end in two opposed wedges 23, their sloping sides facing rearwardly and being convergent, while their forward sides are co-planar and at right angles to the axis of the needle 17. Viewed end-on, as in Figure 3, the wedges 23 form a rectangle slightly smaller than the inner cross-sectional profile of the body 1,2. At the rear end, the jacket is formed with a domed stud 24 with an undercut slot 25 to locate and trap the forward end of the

coil spring 6, which fits over the stud 24.

Initially, the pricker is as shown in Figure 1, with the cap 20 projecting well beyond the forward end of the body 1, 2 but with the tip 19 of the needle still inside the body and encased by the rear end of the cap 20. To prime or cock the trigger, the cap is simply pressed axially towards the body 1 causing the lancet to compress the spring 7. As one of the wedges 23 reaches the hook 12, the sloping surfaces co-operate to rock the trigger 9 until the wedge 23 snaps past the hook 12, whereupon the resilience of the webs 11 and the strips 14 restores the trigger back to the Figure 1 position to trap the lancet in a fully retracted position. The tab 22 is then grasped and, with the body 1 held, is given a twist. The wedges 23 prevent the lancet rotating within the body 1, and so the weak collar 21 is sheared. The cap 20 can then be withdrawn. A thumb or finger is pressed into the aperture 4 and the pad 13 is pressed releasing the lancet. It shoots forward to make the prick and, the spring 7 momentarily having been over extended, draws the lancet back a little so that the tip 19 ends up safely inside the body 1,2.

Although the leading end of the lancet does not have much freedom of movement within the body 1,2 its rear end can shift up and down. The lancet will therefore tend to come to rest slightly skew to the axis of the body 1,2. Certainly, if an attempt is made to retract the lancet again by inserting something through the hole 4, the spring 7 and the lancet will tend to go out of alignment. This makes it



very difficult to use the discarded cap to poke the lancet back for possible re-use. Thus, the pricker and cap will have to be discarded.

CLAIMS

1. A disposable pricker comprising an elongate body with a spring-loaded lancet carried therein, the lancet tip normally being within the body, a trigger mechanism to retain the lancet in a fully retracted position energising the spring means and actuable to release the lancet to cause the tip to have a momentary position projecting from the forward end of the body, and an elongate cap encasing the lancet tip and having a head external of the body, the cap providing means to retract the lancet and being breakable free of the lancet to leave the tip exposed.

2. A disposable pricker as claimed in Claim 1, wherein the trigger mechanism comprises a rocker with an outstanding projecting portion for manual operation and an inwardly projecting portion for co-operation with the lancet.

3. A disposable pricker as claimed in Claim 2, wherein the rocker is centrally connected to the main part of the body by webs which are distortable to allow the rocker action.

4. A disposable pricker as claimed in Claim 3, wherein the rocker has further means connecting it to the body to resist pivoting below a predetermined actuating force.

5. A disposable pricker as claimed in any preceding claim, wherein the trigger mechanism is formed integrally with the body, which is of moulded plastics material.

6. A disposable pricker as claimed in any preceding claim, wherein the lancet has a detent and the trigger has a co-operative lug, projecting inwardly with respect to the body, the detent being arranged to snap past the lug as  
5 the lancet is retracted and to hold the lancet in that position.

7. A disposable pricker as claimed in any preceding claim, wherein the body is moulded in two parts connected by a thin flexible web, presenting the body in an  
10 opened out condition but closeable together when the lancet and spring means are in place.

8. A disposable pricker as claimed in any preceding claim, wherein the lancet has an engagement with the interior of the body preventing it rotating about its  
15 longitudinal axis at least when the lancet is retracted.

9. A disposable pricker as claimed in any preceding claim, wherein the fit of the lancet within the body is such that, once the lancet has been fired, it will lie skew to the axis of the body.




Fig. 1




Fig. 2




Fig. 3

**I. CLASSIFICATION OF SUBJECT MATTER** (if several classification symbols apply, indicate all)<sup>6</sup>

According to International Patent Classification (IPC) or to both National Classification and IPC

Int.Cl. 5 A61B5/14

**II. FIELDS SEARCHED**Minimum Documentation Searched<sup>7</sup>

Classification System

Classification Symbols

Int.Cl. 5

A61B

Documentation Searched other than Minimum Documentation  
to the Extent that such Documents are Included in the Fields Searched<sup>8</sup>**III. DOCUMENTS CONSIDERED TO BE RELEVANT<sup>9</sup>**

Category <sup>10</sup>	Citation of Document, <sup>11</sup> with indication, where appropriate, of the relevant passages <sup>12</sup>	Relevant to Claim No. <sup>13</sup>
X	EP,A,0 427 406 (OWEN MUMFORD, LTD.) 15 May 1991 cited in the application see column 4, line 6 - line 25 see column 5, line 29 - column 6, line 5 see claim 10; figures 9,11,12 ---	1-3,5,6, 8
Y	EP,A,0 433 050 (OWEN MUMFORD, LTD.) 19 June 1991 cited in the application	1,5
A	see column 2, line 54 - column 3, line 2 see column 3, line 42 - line 55; figure 1 ---	6-8
Y	EP,A,0 458 451 (BOEHRINGER MANNHEIM CORP.) 27 November 1991	1,5
A	see column 2, line 41 - column 4, line 15 see column 7, line 19 - line 30 see figures 1-4,8,9 ---	2-4
	---	-/--

<sup>10</sup> Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

**IV. CERTIFICATION**

Date of the Actual Completion of the International Search

02 JULY 1993

Date of Mailing of this International Search Report

13 -07- 1993

International Searching Authority

EUROPEAN PATENT OFFICE

Signature of Authorized Officer

RIEB K.D.

III. DOCUMENTS CONSIDERED TO BE RELEVANT (CONTINUED FROM THE SECOND SHEET)

Category <sup>a</sup>	Citation of Document, with indication, where appropriate, of the relevant passages	Relevant to Claim No.
A	<p>US,A,4 539 988 (G.R. SHIRLEY ET AL.)  10 September 1985  see column 3, line 7 - line 15  see column 4, line 54 - line 58  see figures 7,9</p> <p>---</p>	1-8
A	<p>EP,A,0 255 338 (GLYME VALLEY TECHNOLOGY)  3 February 1988  see figure 6D</p> <p>---</p>	9
A	<p>FR,A,771 890 (L. RIEDMÜLLER)  18 October 1934  see page 2, line 83 - line 93; figures 1,2</p> <p>-----</p>	1,2,4